

# Highland Order/Quote Form

Billing Address:

Shipping Address:

PO Number:

Company:

Name:

Email:

Phone:

	Highland Product Line	Quantity (Gallons)	Product Description	Color Name/Code	Package Size
Primers	15-ZN-4074		HiTemp Silicone Zinc Primer (250°F - 1000°F)		
	250-PR-####		HiTemp Modified Alkyd Primer (Up to 250°F)		
	700-PR-####		HiTemp Modified Silicone Primer (Up to 700°F)		
	802		HiTemp Silicone Alkyd Primer (Up to 500°F)		
	860-HF-####		HiTemp "Universal Hot Mix" Primer (Up to 400°F)		
	830-####		HiTemp <b>Dry-Fall</b> Silicone Alkyd Primer (Up to 400°F)		
	15ZN-DF-####		HiTemp <b>Dry-Fall</b> Silicone Zinc Primer (Up to 1000°F)		
	84-LH-1024		Structural "HiGlo" Alkyd Primer (Ambient)		
	97-HF-5043		Structural High Solids Epoxy Mastic Primer (Ambient)		
	475R####		Structural <b>Dry-Fall</b> Epoxy Primer (Ambient)		
84-DF-1024		Structural <b>Dry-Fall</b> "HiGlo" Alkyd Primer (Ambient)			
Direct-To-Metal	47-HF-####		HiTemp Hybrid Epoxy Novolac DTM (Up to 450°F)		
	500-QD-####		HiTemp Chain Stopped Alkyd DTM (Up to 300°F)		
	79-LH-3097		HiTemp Baghouse Epoxy DTM (Up to 350°F)		
	811-DTM-####		HiTemp Silicone DTM (350°F - 1000°F)		
	812-LH		HiTemp Silicone Alkyd DTM (Up to 600°F)		
	827-HB-####		HiTemp "DuraDrum" Multipolymeric Matrix (Up to 1200°F)		
	899-####		HiTemp Modified Silicone DTM (350°F - 1000°F)		
	827-HB-####		HiTemp <b>Dry-Fall</b> Multipolymeric Matrix (Up to 1200°F)		
	899-DF-####		HiTemp <b>Dry-Fall</b> Modified Silicone DTM (350°F - 1000°F)		
	97-HF-####		Structural High Solids Epoxy Mastic DTM (Ambient)		
200-QD-####		Structural Quick-Dry Chain Stopped Alkyd DTM (Ambient)			
485R####		Structural <b>Dry-Fall</b> Epoxy DTM (Ambient)			
Topcoats	250-TC-####		HiTemp Epoxy Ester Topcoat (Up to 250°F)		
	700-TC-####		HiTemp Modified Silicone Acrylic Topcoat (300°F - 700°F)		
	805-LH-####		HiTemp Modified Silicone Topcoat (250°F - 1000°F)		
	815-####		HiTemp Silicone Acrylic Topcoat (Up to 500°F)		
	865-LH-####		HiTemp "Universal Hot Mix" Silicone Alkyd Topcoat (Up to 400°F)		
	805-DF-####		HiTemp <b>Dry-Fall</b> Silicone Topcoat (250°F - 1000°F)		
	815-DF-####		HiTemp <b>Dry-Fall</b> Silicone Acrylic Topcoat (Up to 500°F)		
	840-G-####		HiTemp <b>Dry-Fall</b> Silicone Alkyd Topcoat (Up to 400°F)		
	36-HF-####		Structural Acrylic Urethane High Gloss Topcoat (Ambient)		
	150C####		Structural "HiGlo" Alkyd Topcoat (Ambient)		
150BR####		Structural "HiGlo" Brush & Roll Alkyd Topcoat (Ambient)			
65-R-####		Structural <b>Dry-Fall</b> Acrylic Topcoat (Ambient)			
68-R-####		Structural <b>Dry-Fall</b> Urethane Topcoat (Ambient)			
Solvents & Additives	34-ALH-100		Urethane Modifier-Adds Gloss, Durability, & Hardness (for use with topcoats only)	N/A	
	100 Reducer		Warm Weather (>80°F) Reducer (For use with HiTemp & HiGlo Products)	N/A	
	120 Reducer		Cold Weather (<80°F) Reducer (For use with HiTemp & HiGlo Products)	N/A	
	901 Cleaner		Powerful Cleaning Solvent For Use on Equipment etc.	N/A	
	30-E		Warm Weather (>80°F) Dry-Fall Reducer	N/A	
	32-E		Cold Weather (<80°F) Dry-Fall Reducer	N/A	
	36-E		Dry-Fall Retarder / Blending Reducer	N/A	
	105		Brush & Roll Reducer	N/A	
	101A		Hot Application Reducer	N/A	
	827-HA		Hot Application Reducer (for 827-HB Series Only)	N/A	
Custom Items					